

A Robust, Economical Choice



PS-3315E

Best Value Fanless POS Terminal

PS-3315E is a 15" touch screen fanless POS Terminal with all the essential functions and capabilities to satisfy businesses of all sizes, and represents one of the best value choices in the entry-level POS Terminal segment.

PS-3315E

Slim and Flexible

Streamlined design equips with a foldable base; PS-3315E provides users with unmatched flexibility to adjust the screen to a height and angle depending on the application.

Expandable and Neat

Designed to better manage peripheral connectivity by separating a full set of ports into the top of the terminal top and the base, PS-3315E ensures neat, reliable peripheral cabling.

Specification	PS-3315E
Processor	Intel J1900 processor, 2.00GHz/2.42GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	1 x SATA + 1 x eMMC connector, 64GB SATA SSD default
Power Supply	12V/30W
OS Support	Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/POSReady 7/Linux per request
Display	
LCD Display	15" TFT LCD, 1024 x 768 resolution
Touch Function	5-wire resistive touch
Connectivity	
LAN Port	10/100/1000Mb x 1
Serial Port	3 x DB9 + 1 x RJ50, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
UPS Port	N/A
Standard USB Port	5
PS/2 Port	1, via optional conversation cable
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
Audio	Buzzer only
WIFI	Optional internal mini-PCle WIFI module with PIFA Antenna
Physical Dimension	
Physical Dimension Dimension (W x D x H in mm)	372 x 320 x 252.7
	372 x 320 x 252.7 5.86
Dimension (W x D x H in mm)	
Dimension (W x D x H in mm)	
Dimension (W x D x H in mm) Weight (N.W. in Kg)	
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment	5.86
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205 SA-305	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205 SA-305 SA-405	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205 SA-305 SA-405 SA-505	5.86 O°C - 40°C, 20%RH - 90%RH (Equipped with HDD); O°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor 3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205 SA-305 SA-405 SA-505 LM-6807U/LM-6810U	5.86 0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor 3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series 7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface)
Dimension (W x D x H in mm) Weight (N.W. in Kg) Environment Operation Condition Storage Condition Options SA-105 SA-205 SA-305 SA-405 SA-505 LM-6807U/LM-6810U PD-2609UE	5.86 O°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD) -20°C - 70°C, 10%RH - 90%RH Side Attachment for PS Series with 3 track MSR Side Attachment for PS Series with iButton Side Attachment for PS Series with support for 3 track MSR, RFID and Finger Print Sensor Side Attachment for PS Series with support for 3 track MSR, 3G dongle and Finger Print Sensor 3-in-1 attachment with MSR (default), RFID & iButtonsupport for 15"/17" XT series & 15"/15.6" PS series 7" 800 x 480 / 10" 1024 x 768 rear-mount 2nd display for PS series (USB interface) 2 x 20 VFD, rear-mount, USB with Virtual COM support

^{*} The product information and specifications are subject to change without prior notice.
* Please refer to the web site for more attachment options.

U.S Patent 9004436

2016Q1













Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.

POSIFLEX TECHNOLOGY INC.

No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan Fax: +886-2-2299-1819

www.posiflex.com



Authorized Distributor / Reseller